



Low Ash GAS ENGINE OIL

CHAMPION LOW ASH ENGINE OIL is a tough duty low phosphorus and sulfur mono-grade engine oil chemically engineered to control deposits, wear, and oxidation in naturally aspirated and turbo charged engines.

Features include:

- Extended thermal and oxidation protection
- Premium low ash anti-wear and cold flow protection.
- Helps maintain a super clean engine
- Universal fluid compatibility among many manufacturer's engines

CHAMPION LOW ASH ENGINE OIL is recommended for service fill in low to medium speed four stroke and select two stroke stationary engines fueled by natural or synthetic gas. Used in engines manufactured by;

Four Stroke Engines

- Ajax
- Arrow
- Cooper
- Diabema
- Kubota
- Superior
- Waukesha
- Worthington

Two Stroke Engines

- Ajax
- Clark Dresser
- Fairbanks-Morse/MEP
- Worthington

See Your Owners Manual for Viscosity Recommendation

TYPICAL SPECIFICATION

SAE Grade	20	30	40
Product Code	4034	4032	4031
MSDS #	100	100	100
Gravity API @ 60° F	30.5	27.9	26.9
Pour Point ° F	-18	-14	-10
Flash Point ° F	428	440	464
cSt @ 40°C	50.0	95.0	127.0
cSt @ 100°C	7.0	10.7	13.0
TBN, mg KOH/gm	6.0	6.0	6.0
Sulfated Ash %wt	0.50	0.50	0.50
Viscosity Index	95	95	95

Call Our Friendly Sales Representatives for Available Package Sizes

4031 4032 4034

EFFECTIVE 02/10

**CHAMPION BRANDS, L.L.C. • 1001 Golden Drive • Clinton, MO 64735
ORDER DESK 800-821-5693**