



SYNTHETIC BLEND

2-CYCLE POWER EQUIPMENT OIL

with FUEL STABILIZER

2 CYCLE POWER EQUIPMENT OIL is our premium quality ashless motor oil for use in 2-cycle air cooled engines. This specially formulated oil meets the lubrication and high temperature demands of air cooled engines by combining Group II base oils and pure isobutene, rather than commonly used fragmented isobutene which can degrade faster at high temperatures. In addition, it contains several semi-synthetic additives providing excellent detergency and dispersant to provide protection and performance requirements of leading engine manufacturers including;

- BOLENS
- CRAFTSMAN
- CUB CADET
- ECHO
- HOMELITE
- HONDA
- HUSQVARNA
- IDC
- JOHN DEERE
- LAWNBOY
- MAKITA
- McCULLOUGH
- RED MAX
- ROBIN SOLO
- RYAN
- RYOBI
- SHINDAIWA
- STIHL
- TANAKA
- TMC
- TORO
- TROY BILT
- WEEDEATER

Additional benefits include:

- Super tough film oil protects against engine wear, and corrosion.
- Anti-foaming and superior anti-scuffing protection
- Synthetic Blend with Fuel Stabilizer
- Increases performance by reducing engine deposits, carbon and spark plug fouling.
- Blended to provide anti-smoke performance to meet any state, national, or international regulatory requirements.

Recommended for use where manufacturer specifications require 2-Cycle oil to meet performance requirements of;

- **API TC**
- **JASO FD**
- **ISO-L-EGD**
- **TISI**

Mix only according to the manufacturer's recommended mixing ratio.

| TYPICAL PROPERTIES | |
|---------------------------|-------------|
| Product Code | 4115 |
| MSDS # | 200 |
| Color | Green |
| Gravity API @ 60°F | 32.9 |
| cSt @ 40°C | 46.8 |
| cSt @ 100°C | 8.4 |
| SUS @ 104°F | 315 |
| SUS @ 210°F | 54 |
| Viscosity Index | 150 |
| Pour Point °F | -37 |
| Flash Point °F | 140 |

Call Our Friendly Sales Representatives for Available Package Sizes

4115

EFFECTIVE 11/08