



# Synthetic Blend 2-Cycle Power Equipment Oil

2 CYCLE POWER EQUIPMENT OIL is our premium quality low-smoke motor oil for air-cooled 2 stroke engines.

## Provides lubricity, anti-wear, and anti-oxidation performance

- Super tough film oil protects against engine wear, and corrosion
- Anti-foaming and superior anti-scuffing protection
- Increases performance by reducing engine deposits, carbon and spark plug fouling
- Blended to provide anti-smoke performance to meet any state, national, or international regulatory requirements

This specialty oil is formulated with severely hydrotreated base oils and synthetic fluid polymer to be cleaner burning than standard solvent-refined oils. Our premium additive chemistry provides detergent and dispersant chemistry to prevent fouling or gumming of 2 stroke engine components. It also provides lubricity, anti-wear, and anti-oxidation performance required for hot-running, air-cooled power equipment engines. In addition, it contains several semi-synthetic additives providing excellent detergency and dispersant to provide protection and performance requirements of leading engine manufacturers including;

- BOLENS
- CRAFTSMAN
- CUB CADET
- ECHO
- HOMELITE
- HONDA
- HUSQVARNA
- JOHN DEERE
- LAWNBOY
- MAKITA
- McCULLOUGH
- RED MAX
- ROBIN SOLO
- RYAN
- RYOBI
- SHINDAIWA
- STIHL
- TANAKA
- TMC
- TORO
- TROY BILT
- IDC
- WEEDEATER

### Directions:

Mix only according to the manufacturer's recommended mixing ratio.

**Recommended for use where manufacturer specifications require 2-Cycle oil to meet performance requirements of; API TC, JASO FD, ISO-L-EGD, and TISI.**

### Typical Values:

Product Code	4115
MSDS #	200
Color	Green
Gravity API @ 60°F	32.9
Flash Point, °C (°F)	40.5 (105)
Pour Point °C °F	- 37 (- 38 )
cSt @ 40 °C	46.8
cSt @ 100 °C	8.4
SUS @104 °F	315
SUS @210 °F	54
Viscosity Index	150



**4115**  
**Effective 03/12**