



ALLTRANS™ FLEET

Synthetic Automatic Transmission Fluid

Champion® AllTrans™ Fleet Synthetic ATF is a universal fluid of exceptional quality. Delivers smooth shifting and excellent anti-shudder performance in a wide variety of passenger cars, municipal or transit buses, garbage haulers, motor homes, delivery vans, emergency vehicles, school buses, dump trucks, utility vehicles, cement trucks, line haul trucks and tow trucks. Recommended replacement fluid in Allison 1000, 2000, 2000MH, 2400, B300, B400, B500, HD4060, HD4560, MD3060, MD3066, MD3560, MT643, MT647 and MT648 transmissions. This is the toughest and most diverse automatic transmission fluid available delivering premium performance and protection. Guaranteed!

- Formulated for the Allison TES-295 transmission fluid specification
- Replaces Allison/Castrol Transynd® fluid
- Excellent protection in temperature extremes
- Prevents clutch glazing and elongated shift times.
- Exceptional shear stability, superior wear protection, and longer fluid service life.

Champion® AllTrans™ Fleet Synthetic ATF

meets or exceeds the requirements of:

- Allison TES-295, C-4
- Caterpillar TO-2 (obsolete)
- Chrysler ATF+3, ATF+4 Specifications
- Denison HF-0
- Ford MERCON® V, MERCON®
- GM DEXRON®-III (H), DEXRON®-II
- Sundstrand Hydrostatic Transmissions
- Vickers M-2950-S and I-286-S
- Voith DIWA Transmissions
- ZF TE-ML 14C, Ecomat Transmissions

Champion® AllTrans™ Fleet-Synthetic ATF

Is also recommended replacement fluid for;

Ford	PN XT-8-QAW
General Motors	PN 88900925
Toyota	PN 08886-00405
Toyota/Lexus/Scion	PN 08886-81015
Porsche	PN 000 043 205 28
Saturn	PN 22689186
Volvo	PN 1161540-8

TYPICAL PROPERTIES

SAE Grade	20W
Product Code	4357
MSDS #	400
Gravity API @ 60°F	32.0
cSt @ 40°C	35.0
cSt @ 100°C	7.6
cP @ -40°C	<8,500
SUS @ 104°F	172
SUS @ 210°F	51
Viscosity Index	>190
Pour Point °F	<-50
Flash Point °F	>440
Color	Red

WARNING:

DO NOT USE IN PLACE OF

- GM Dexron® VI Transmission Fluid
- Ford Mercon® SP Transmission Fluid
- Ford Mercon® CVT Transmission Fluid
- Ford Type F Transmission Fluid

Where extended drain intervals are recommended by the OEM, follow that recommendation. This includes the recommendations set by Allison® in document #10-TR-99 Rev. B, January 2002, for TES-295 fluids. Because Champion® AllTrans™ Fleet Synthetic ATF it is not specifically designated by Allison® as a TES-295 product, the Champion AllTrans Fleet Synthetic ATF Limited Warranty (see reverse side) will cover all lubricant related failures.

Call Our Friendly Sales Representatives for Available Package Sizes

4357

EFFECTIVE10/07

CHAMPION BRANDS, L.L.C. • 1001 Golden Drive • Clinton, MO 64735
ORDER DESK 800-821-5693

Champion® AllTrans™ Fleet Synthetic ATF Limited Warranty

This is a limited warranty covering the Champion AllTrans Fleet lubricant you purchased. Champion Brands, LLC warrants its lubricants to be free from defects and will replace any Champion Brands lubricant that is defective. For vehicles covered by a warranty, follow the vehicle's change interval recommended in your owner's manual. Follow your owner's manual if the vehicle is operated in any of the following severe services: racing or commercial applications including taxis, limousines, etc.; frequent towing or hauling; extremely dusty or dirty conditions; or under excessive idling conditions. If your vehicle has exceeded the duration of the manufacturer's warranty, Champion Brands warrants that the Champion AllTrans Fleet lubricant you purchased will protect your vehicle's critical transmission parts from fluid related failure only if the recommendations in your owner's manual are followed. Champion Brands, LLC provides this limited warranty to the purchasers who use Champion AllTrans brand lubricants in their vehicle.

This limited warranty covers the Champion AllTrans brand lubricant and critical transmission parts lubricated by the lubricant.

If there is equipment failure related to the Champion AllTrans brand lubricant you purchased, Champion Brands, LLC will repair any equipment damage directly caused by a defect or malfunction of a Champion AllTrans lubricant, provided that the lubricant was maintained in accordance with specifications of the original equipment manufacturer or the written instructions (which includes product packaging) of Champion Brands, LLC.

To file a claim under this Limited Warranty, you must:

- Upon discovery of the damage (but not later than six (6) months from the date the damage occurred) call 1-800-821-5693.
- Allow a Champion Brands, LLC representative to examine the equipment and maintenance records, if available, and provide proof of purchase to determine the extent of the damage and to confirm that a Champion AllTrans lubricant was the cause.
- Allow a Champion Brands, LLC representative to obtain a lubricant sample from the transmission for analysis at no cost to you to assist in determining the cause of the equipment failure.

This Limited Warranty excludes:

- Champion Brands, LLC lubricants used in mechanically deficient equipment as a result of abnormal operation; negligence; abuse; damage from casualty, shipment or accident; or, equipment modification done without written authorization from the OEM.
- Situations where the OEM required lubricant standards do not match those stated by Champion AllTrans without written approval from Champion Brands, LLC.
- Champion AllTrans lubricants that have been used in conjunction with any other product or additive that has not been authorized for use by Champion Brands, LLC.
- Failure of equipment due to a pre-existing condition that is unrelated to the use of Champion AllTrans lubricants.
- Repair or replacement of equipment due to normal wears.

The remedy provided here will be your only recovery against Champion Brands, LLC. You will not be able to recover incidental or consequential damages. Some states do not allow the exclusion of or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.