



Champion® SynClean™ 7500 synthetic blend motor oils guarantee* protection for 7,500 miles. It extends engine life by significantly reducing wear and viscosity breakdown through pioneering advancements in oil technology. Champion's SynClean additive system in combination with Champion's premium performance racing fluids outperform *all* previous engine oils providing improvements in engine cleanliness, fuel economy, and lubrication film strength for superior protection between moving parts, even at extreme engine temperatures or during longer drain intervals.

Features include:

- Lower pour point pumps fluid faster to moving parts reducing wear during the coldest Winter season
- Excellent wear protection and engine cleanliness at oil temperatures of 400°F, even at longer drain intervals
- Helps reduce oil consumption and improve fuel economy using the power of synthetic blend fluid
- Recommended oil for gasoline and turbocharged gasoline engines with exchange gas recirculation (EGR) systems and/or catalytic exhaust conversion systems
- Protects against engine sludge, varnish deposits and resists thermal viscosity breakdown
- Compatible with conventional oils

Champion® SynClean™ 7500 Synthetic Blend motor oils are approved and recommended for service fill by General Motors, Ford Motor Company, DaimlerChrysler, in use in Acura, Chrysler, Ford, GMC, Honda, Infiniti, Isuzu, KIA, Lexus, Lincoln, Mercury, Mercedes Benz, Mitsubishi, Saturn, Toyota and Volvo cars and light duty trucks. See *OEM Manual for Viscosity Recommendation*

TYPICAL SPECIFICATION

SAE Grade	5W-20	5W-30	10W-30
Product Code	4230	4231	4232
MSDS #	100	100	100
API Service / ILSAC	SM / GF-4	SM / GF-4	SM / GF-4
General Motors	GM 9986202	GM 9986231, GM 6094M	GM 9986126, GM 6094M
DaimlerChrysler	MS-6395NL, DC MS10797	MS-6395N/L, DC MS10796	MS-6395N/L, DC MS10798
Ford Motor Company	WSS- M2C930-A, M2C153-H	WSS- M2C929-A, M2C153-G	WSS- M2C205-A, M2C153-G
Gravity API @ 60° F	34.0	33.0	33
Pour Point °F	-49	-44	-33
Flash Point °F	435	440	450
cSt @ 100°C	8.6	10.4	10.4
cSt @ 40°C	48.8	60.5	61.8
Cold Crank Visc, cP	< 6,600 @ -30°C	< 6,600 @ -30°C	< 7,000 @ -25°C
Viscosity Index	155	162	158
SUS @ 212°F	54	61	61
SUS @ 104°F	222	280	287
TBN, mg KOH/gm	8.2	8.2	8.2
Color	Amber	Amber	Amber

Call Our Friendly Sales Representatives for Available Package Sizes

4230 4231 4232

EFFECTIVE 05/05

*See Champion® SynClean™ 7500 Synthetic Blend Motor Oil Limited Warranty (Over)

CHAMPION BRANDS, L.L.C. • 1001 Golden Drive • Clinton, MO 64735
ORDER DESK 800-821-5693

Champion® SynClean™ 7500 Synthetic Blend Motor Oil Limited Warranty

This is a limited warranty covering the Champion SynClean 7500 lubricant you purchased. Champion Brands, LLC warrants its lubricants to be free from defects and will replace any Champion Brands lubricant that is defective. For vehicles covered by a warranty, follow the vehicle's oil life sensor or the oil change interval recommended in your owner's manual. Follow your owner's manual if the vehicle is operated in any of the following severe services: racing or commercial applications including taxis, limousines, etc.; frequent towing or hauling; extremely dusty or dirty conditions; or under excessive idling conditions. If your vehicle has exceeded the duration of the manufacturer's warranty, Champion Brands warrants that the Champion SynClean 7500 lubricant you purchased will protect your vehicle's critical engine parts from oil related failure for 7,500 miles or 6 months, whichever ever comes first. If not, provided the engine was serviceable at the time the oil was installed, Champion Brands will have your vehicle repaired and replace the oil at no cost to you.

Champion Brands, LLC provides this limited warranty to the purchasers who use Champion SynClean brand lubricants in their vehicle.

This limited warranty covers the Champion SynClean brand lubricant and critical engine parts lubricated by the lubricant.

This limited warranty is valid for 7,500 miles or 6 months from the date [purchase or installation], whichever is earlier.

If there is equipment failure related to the Champion SynClean brand lubricant you purchased, Champion Brands, LLC will repair any equipment damage directly caused by a defect or malfunction of a Champion SynClean lubricant, provided that the lubricant was selected and maintained in accordance with specifications of the original equipment manufacturer or the written instructions (which includes product packaging) of Champion Brands, LLC.

To file a claim under this Limited Warranty, you must:

- Upon discovery of the damage (but not later than six (6) months from the date the damage occurred) call 1-800-821-5693.
- Allow a Champion Brands, LLC representative to examine the equipment and maintenance records, if available, and provide proof of purchase to determine the extent of the damage and to confirm that a Champion SynClean lubricant was the cause.
- Allow a Champion Brands, LLC representative to obtain an oil sample from the engine for oil analysis at no cost to you to assist in determining the cause of the equipment failure.

This Limited Warranty excludes:

Champion Brands, LLC lubricants used in mechanically deficient equipment as a result of abnormal operation; negligence; abuse; damage from casualty, shipment or accident; or, equipment modification done without written authorization from the OEM.

Situations where the OEM required lubricant standards do not match those stated by Champion SynClean without written approval from Champion Brands, LLC.

Champion SynClean lubricants that have been used in conjunction with any other product or additive that has not been authorized for use by Champion Brands, LLC.

Failure of equipment due to a pre-existing condition that is unrelated to the use of Champion SynClean lubricants.

Repair or replacement of equipment due to normal wears.

The remedy provided here will be your only recovery against Champion Brands, LLC. You will not be able to recover incidental or consequential damages. Some states do not allow the exclusion of or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

TYPICAL 2004 PASSENGER CAR ENGINE OIL DRAIN FILTER CHANGE INTERVALS

Vehicle Manufacturer	Normal Service *	Severe Service *
Acura	7,500 Miles / 12 Months	3,750 Miles / 6 Months
Audi	10,000 Miles	5,000 Miles
BMW	Use Service Indicator	Use Service Indicator
Chrysler/Dodge/Dodge Trucks/Jeep	6,000 Miles / 6 Months	3,000 Miles / 3 Months
Ford/Lincoln/Mercury/Ford Trucks	5,000 Miles	3,000 Miles
General Motors	7,500 Miles	3,000 Miles
Honda	7,500 Miles / 12 Months	3,750 Miles / 6 Months
Hyundai	7,500 Miles / 6 Months	3,000 Miles / 3 Months
Infiniti	7,500 Miles / 6 Months	3,750 Miles / 3 Months
Isuzu	7,500 Miles / 12 Months	3,000 Miles / 6 Months
Jaguar	10,000 Miles	10,000 Miles
KIA	7,500 Miles / 7.5 Months	5,000 Miles / 5 Months
Lexus	7,500 Miles	5,000 Miles
Mazda	7,500 Miles	5,000 Miles
Mitsubishi	7,500 Miles / 12 Months	3,000 Miles / 6 Months
Nissan	7,500 Miles / 6 Months	3,750 Miles / 3 Months
Porsche	12,000 Miles	12,000 Miles
Saab	10,000 Miles	10,000 Miles
Subaru	7,500 Miles / 12 Months	3,750 Miles / 3 Months
Suzuki	7,500 Miles	3,000 Miles
Toyota	7,500 Miles	5,000 Miles
Volkswagen	10,000 Miles	5,000 Miles
Volvo	7,500 Miles	7,500 Miles

*Source: 2004 Chek-Chart Car Care Guide.