

CHAMPION PDS

PRODUCT DATA SHEET

PROFESSIONAL GRADE SNOW PLOW OIL

CHAMPION Professional Grade Snow Plow Oil is a long-life hydraulic oil formulated with severely hydrotreated and hydrofinished API Group II base oils for improved oxidation resistance, viscosity retention and cold flow properties. This oil has excellent viscosity retention and cold-flow due to a very high viscosity index. Excellent protection against wear, corrosion and the build-up of sludge and varnish in the most demanding snowplow applications.

- Extended fluid life for longer service intervals
- High thermal and oxidation stability
- Top-tier anti-wear performance
- Excellent filterability and cleanliness
- Excellent demulsibility and air release
- Excellent cold-flow properties

Champion Professional Grade Snow Plow Oil meets or exceeds the following:

- Parker (Denison) HF-0, HF-1, HF-2
- MAG (CM) P-68 (ISO 32), P-69 (ISO 46), P-70 (ISO 68)
- GM LS-2
- Joy HO-T, HO-S, HO-T2
- AIST (US Steel) 126, 127
- DIN 51524-3, Type HLVP
- ASTM D6158, Type HV
- ISO 6743/4, Type HV
- Eaton M-2950-S, I-286-S3
- Bosch Rexroth RE 90220
- SEB 181222
- AFNOR NF E 48-603 (HV)
- SAE MS 1004, Type HV
- ANSI/AGMA 9005-E02-RO
- ISO 11158, Type HV

PART# 4013

Available in:

4013H - 1 Quart



TYPICAL PROPERTIES:

PRODUCT CODE:	4013
GRAVITY API @ 60°F	27.8
VISCOSITY @ 40°C, cSt	14.56
VISCOSITY @ 100°C, cSt	4.25
VISCOSITY INDEX	224
DENSITY #/GAL	7.4

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at WWW.CHAMPIONBRANDS.COM

CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20

