

# CHAMPION PDS

PRODUCT DATA SHEET

## LOW ASH ENGINE OIL

CHAMPION Low Ash Engine Oils are high viscosity index, paraffinic engine oils with low ash content, good cold-flow properties, and a unique blend of anti-oxidants to provide for long service life and system cleanliness. Champion additive technology provides excellent anti-wear and anti-oxidant properties, dispersancy, and moderate alkalinity needed for 2-stroke and 4-stroke natural and pipeline gas engines.

- High viscosity index and excellent cold-flow properties
- Excellent dispersancy and sludge control
- Synergistic anti-oxidant technologies provide superior resistance to oil oxidation
- Detergent and anti-oxidant system fight harmful oil nitration and acid build-up
- Good anti-wear performance
- Low foam formula
- Moderate alkalinity for normal service quality gas - not recommended for sour or landfill gas

Recommended for use in low and medium speed stationary gas engines, including those manufactured by: • Ajax • Kobuta • Arrow • Cooper • Diabema • Superior • Waukesha • Worthington • Clark-Dresser  
Consult your equipment manual for correct viscosity grade

**PART# 4032 - SAE 30**

**PART# 4034 - SAE 20**



### TYPICAL PROPERTIES:

PRODUCT CODE:	4032
SAE GRADE	30
GRAVITY API @ 60°F	29.5
SPECIFIC GRAVITY	0.8791
LBS/GAL	7.32
POUR POINT °F	-14
VISCOSITY @ 40°C, cSt	102
VISCOSITY @ 100°C, cSt	12.2
VISCOSITY INDEX	110
SULFATED ASH (% WT)	0.50
TBN, mg KOH/g	5.0

PRODUCT CODE:	4034
SAE GRADE	20
GRAVITY API @ 60°F	31
SPECIFIC GRAVITY	0.8713
LBS/GAL	7.26
POUR POINT °F	-18
VISCOSITY @ 40°C, cSt	62
VISCOSITY @ 100°C, cSt	8.5
VISCOSITY INDEX	110
SULFATED ASH (% WT)	0.50
TBN, mg KOH/g	5.0

#### Available in:

4032U	-	2.5 Gallon
4032AN	-	55 Gallon
4034U	-	2.5 Gallon

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at [WWW.CHAMPIONBRANDS.COM](http://WWW.CHAMPIONBRANDS.COM)

CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20

