CHAMPION PDDS PRODUCT DATA SHEET

SYNTHETIC-BLEND 2-CYCLE POWER EQUIPMENT OIL

CHAMPION Synthetic Blend 2-Cycle Power Equipment Oil is a Specialty semi-synthetic, low ash engine oil designed for the demands of modern two cycle engines found in landscaping industry, Champion Power Equipment 2-Cycle Oil provides exceptional performance in the most demanding applications. Designed specifically to protect equipment and maximize the life of engines, exhaust systems and spark plugs and to maximize uptime and productivity.

- Exceeds the JASO FD, ISO-L-EGD, API TC and TISI performance standards
- Exceeds OEM requirements for small 2-cycle gasoline engines
- Outperforms major OEM fluids in spark plug deposit testing
- Exceptional cleanliness and protection of engines, pistons, plugs and exhaust systems
- More than 7% improvement over JASO FD requirements for detergency
- More than 12% improvement over JASO FD requirements for piston cleanliness
- More than 100% improvement over JASO FD requirements for exhaust system cleanliness
- Contains fuel stabilizer to prevent gum formation in stored, pre-mixed fuel
- Convenient sizes premeasured for 1 gallon, 2.5 gallon or 5 gallon fuel oil mixtures (50:1)

This product is not recommended for use in STIHL 4-MIX engines.



PRODUCT MEETING JASO M345 COMPANY GUARANTEEING THIS FD PERFORMANCE CHAMPION BRANDS, LLC

PART# 4115

Available in:			
4115L	-	2.56 Oz.	
4115J	-	6.4 Oz.	
4115K	-	12.8 Oz.	
4115N	-	1 Gallon	
4115D	-	5 Gallon	
4115AN	-	55 Gallon	

TYPICAL PROPERTIES:

PRODUCT CODE:	4115
VISCOSITY @ 40°C, cSt	83.62
VISCOSITY @ 100°C, cSt	11.43
VISCOSITY INDEX	128
SULFATED ASH, %wt	0.05
POUR POINT °C	-21
FLASH POINT PM °C	100
FLASH POINT PM °C	100

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at WWW.CHAMPIONBRANDS.COM



CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20