

CHAMPION PDS

PRODUCT DATA SHEET

SYNTHETIC-BLEND CLASSIC & MUSCLE OIL

CHAMPION CLASSIC & MUSCLE synthetic blend motor oils contain high levels of premium ZDDP anti-wear protection required in hot rod, muscle, vintage, and classic cars. Especially those using flat tappet or roller cams operating at high RPMs and requiring high-pressure (stiff) valve springs.

CHAMPION CLASSIC & MUSCLE synthetic blend motor oils contain Champion's exclusive TVS® (Thermal Viscosity Stabilizer) technology delivering unmatched film strength at high temperature, better piston ring seal for maximum compression, and increases the foot-pounds of torque in most engines. These oils also contain special lubricity modifiers to reduce friction which unlock the full potential of any engine.

Features:

- Offers film strength and viscosity stability at higher temperatures
- Formulated for the protection of pushrod, flat tappet, and roller cam engines
- Maintains oil pressure and compression at high temperatures
- Provide upper cylinder anti-wear protection
- Universal compatibility with other petroleum and synthetic oils
- Top choice for engine storage

PART# 4124 - 20W-50

PART# 4130 - 10W-30

Available in:

4124H	-	1 Quart
4124AN	-	55 Gallon
4130H	-	1 Quart
4130AN	-	55 Gallon



TYPICAL PROPERTIES:

PRODUCT CODE:	4124
SAE GRADE	20W-50
API	SJ
COLOR	BLUE
LBS/GAL	7.29
GRAVITY	0.876
VISCOSITY @ 100°C, cSt	17.5
ZINC	1600 PPM
CALCIUM	2200 PPM
PHOSPHORUS	1400 PPM
FLASH POINT, °C (°F)	232 (450)
POUR POINT, °C (°F)	-29 (-20)

PRODUCT CODE:	4130
SAE GRADE	10W-30
API	SJ
COLOR	BLUE
LBS/GAL	7.23
GRAVITY	0.864
VISCOSITY @ 100°C, cSt	12.0
ZINC	1600 PPM
CALCIUM	2200 PPM
PHOSPHORUS	1400 PPM
FLASH POINT, °C (°F)	227 (440)
POUR POINT, °C (°F)	-37 (-34)

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at WWW.CHAMPIONBRANDS.COM

CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20

