

# CHAMPION PDS

PRODUCT DATA SHEET

## SYN CLEAN SYNTHETIC-BLEND ENGINE OIL

Champion SynClean engine oils are blended with a premium blend of base oils and specially selected additives to provide modern gasoline engines with superior protection against wear, sludge, varnish, deposits, and oxidation. They also protect against oil-related stochastic pre-ignition (SPI or LSPI) in turbocharged, direct-injection gasoline engines (TGDI).

- Protects against oil-related engine knock in direct-injected, turbocharged engines
- Reduces timing chain wear
- Protects against soot-induced wear
- Excellent protection against sludge, varnish and engine deposits
- Resists oxidation and protects turbocharger bearings



Champion® SynClean engine oils are approved for use in General Motors, Ford and Daimler Chrysler flex-fuel vehicles using either gasoline or E-85. Additional service fill approvals also include Acura, Honda, Infiniti, Isuzu, KIA, Lexus, Mercedes Benz, Mitsubishi, Saturn, Toyota and Volvo cars and light duty trucks. See OEM Manual for Viscosity Recommendation.

### PART# 4141

#### TYPICAL PROPERTIES:

PRODUCT CODE:	4141
SAE GRADE	5W-40
KV @ 40°C	62.9
KV @ 100°C	10.52
VISCOSITY INDEX	157

#### Available in:

4141H	-	1 Quart
4141N	-	1 Gallon

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at [WWW.CHAMPIONBRANDS.COM](http://WWW.CHAMPIONBRANDS.COM)

CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20

