

# CHAMPION PDS

PRODUCT DATA SHEET

## UNIVERSAL AUTOMATIC TRANSMISSION FLUID

CHAMPION Universal Automatic Transmission Fluid is a cost-effective solution for planetary automatic transmissions in passenger motor vehicles, power transmissions in some vocational equipment, certain power steering systems, and anti-wear hydraulic applications. This fluid is blended with quality base oils, shear stable polymer, and carefully balanced chemistry providing friction modification, cleanliness, air release, seal compatibility and resistance to corrosion, oxidation, and wear.

### Benefits and Features:

- Excellent cleanliness; resistance to sludge and varnish buildup
- Anti-wear performance and friction modification
- Exceptional performance at low temperatures
- Friction modification for smooth clutch engagement
- High viscosity index

Champion® Universal Automatic Transmission Fluid meets the performance requirements of:

Allison C-3 & C-4 / Allison TES-389B / American Motors ATF +3 (MS7176-E), ATF +4 (MS9602) / Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A) / Audi G 052 162-A1/A2 (ZF Lifeguardfluid 5) / BMW LA2634 / BMW LT71141 (ZF 5 HP 18FL /19FL/24A) / BMW ZF 5HP18FL, 5HP24, 5HP30 / BMW 7045E / BMW ETL-8072B / Bosch TE-ML 09 / CAT TO-2 Chrysler ATF+, +2, +3 (MS 7176E), +4 (MS 9602) / Daewoo LT 71141 / Esso LT 71141 / Ford MERCON® / Ford ESP-M2C166H, XL-12 / GM TASA / GM DEXRON®-II / GM DEXRON®-IID / GM DEXRON®-IIE / GM DEXRON®-IIIG / GM DEXRON®-IIIH / Hyundai/Kia Dex-II/ SP-II / Jaguar ATF 3403 M115 / Jaguar ATF LT71141, ZF 5HP24 / Jaguar ATF 3403 JLM20238 / JEEP ATF+3, +4 / MAN 339A / Mazda ATF D-II / Mazda ATF M-III / Mazda ATF F-1 / MB ZF 4HP20 / NAG 1 (Chrysler, Jeep, Cherokee) / Opel (all vehicles) / Peugeot/Citreon Z 000169756 / Porsche ZF 5HP19FL, ZF 5HP20, LT71141 / Porsche ATF 3403-M115 / Porsche 000 043 205 09 / Porsche 999 917 547 00 (A2) / PSA / Renault DPO/AL4 Renault Matic D2 / Shell 3403, M115, LA 2634 / Texaco 7045-E / Texaco 8072B / Toyota ATF D-II / Toyota ATF D-III Vickers M2950-S, I-286-S / Volvo 97325 / Volvo 97335 / Volvo CE 97340 / Volvo CE 97341 / VW G-052 025 A2 / VW G-052 162 / ZF all 3 & 4 speed transmission / ZF TE-ML 05L / ZF TE-ML 09 / ZF TE-ML 21L

Not to be used for DCT or CVT applications.  
The above applications are recommended by the oil company, and not by the OEMs, except where approvals are obtained.

## PART# 4355

### Available in:

4355H	-	1 Quart
4355N	-	1 Gallon
4355U	-	2.5 Gallon
4355D	-	5 Gallon
4355AN	-	55 Gallon



## TYPICAL PROPERTIES:

PRODUCT CODE:	4355
SAE GRADE	SAE 20
ISO GRADE	ISO 32
LBS/GAL	7.18
GRAVITY API @60°F	32.7
SPECIFIC GRAVITY	0.862
VISCOSITY @ 40°C, cSt	34.0
VISCOSITY @ 100°C, cSt	7.1
VISCOSITY INDEX	175
BROOKFIELD @ -40°C, cP	15000

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at [WWW.CHAMPIONBRANDS.COM](http://WWW.CHAMPIONBRANDS.COM)

CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20

