

CHAMPION PDS

PRODUCT DATA SHEET

CHAMPION POLY 7® HIGH TEMP GREASE

CHAMPION POLY 7® HIGH TEMP GREASE is made using highly refined petroleum stocks, co-polymers and advanced lithium complex additives specially processed to provide the ultimate in lubrication. The super tough film strength of POLY 7® HIGH TEMP GREASE stays put under extreme shock loads and offers a very low friction coefficient.

RECOMMENDED FOR: All NLGI #2 Applications

Marine Equipment
Boat Trailer Wheel Bearings
Disc Brakes
King Pins
Mining Equipment
Construction Equipment
Farm Equipment
Ball and U-Joints
Chassis Lubrication
Lawn and Garden Equipment
Fifth Wheels

PART# 4050

Available in:

4050T	-	14 Oz Tube
4050D	-	35# Keg
4050C	-	120# Drum
4050AN	-	400# Drum

TYPICAL PROPERTIES:

NLGI GRADE:	2
PRODUCT CODE:	4050
PENETRATION @ 77°F	
WORKED 60	265-295
THICKENER TYPE	LITHIUM
THICKENER CONTENT, %	8-10
DROPPING POINT, °F	520 MIN
BASE OIL VISCOSITY, CST @40°C	132-168
VISCOSITY INDEX	90 MIN
COLOR	GREEN
APPEARANCE	SMOOTH TACKY
TIMKEN OK LOAD LBS	60 MIN
RUST PREVENTION	PASS
FOUR BALL EP WELD LOAD KG	500 MIN
LOAD WEAR INDEX KFG	60 MIN
FOUR BALL WEAR SCAR DIA. MM	0.5 MAX
WATER WASHOUT, %	<10



FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at WWW.CHAMPIONBRANDS.COM

CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956



REV 01/20