CHAMPION PDDS PRODUCT DATA SHEET

CHAMPION POLY 7® RED TACKY GREASE

CHAMPION POLY 7® RED TACKY HIGH TEMP GREASE is a tacky, multi-purpose, high temperature grease that incorporates polymer technology, premium additive technology, hydro-treated base oils and a lithium complex thickening system. Additive and polymer technologies ensure maximum lubricity and adhesion, resistance to water wash-out, and resistance to sling-off. Tackiness additives keep this grease in place under high pitch line speeds, and provide ease of application.



RECOMMENDED FOR: All NLGI #2 Applications

Marine Equipment Boat Trailer Wheel Bearings Disc Brakes King Pins Mining Equipment Construction Equipment Farm Equipment Ball and U-Joints Chassis Lubrication Lawn and Garden Equipment Fifth Wheels

PART# 4053

Available in:

| 4053T | - | 14 Oz Tube |
|-------|---|------------|
| 4053D | - | 35# Keg |
| 4053C | - | 120# Drum |

TYPICAL PROPERTIES:

| NLGI GRADE: | 2 |
|-------------------------------|---------------|
| PRODUCT CODE: | 4053 |
| PENETRATION @ 77°F | |
| WORKED 60 | 265-295 |
| THICKENER TYPE | LITHIUM |
| THICKENER CONTENT, % | 8-10 |
| DROPPING POINT, °F | 520 MIN |
| BASE OIL VISCOSITY, CST @40°C | 292.348 |
| VISCOSITY INDEX | 90 MIN |
| COLOR | RED |
| APPEARANCE | SMOOTH |
| | TACKY |
| TIMKEN OK LOAD LBS | 70 MIN |
| RUST PREVENTION | PASS |
| FOUR BALL EP WELD LOAD KG | 500 MIN |
| LOAD WEAR INDEX KFG | 60 MIN |
| FOUR BALL WEAR SCAR DIA. MM | 0.5 MAX |
| WATER WASHOUT, % | <5.0 |
| | |

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at WWW.CHAMPIONBRANDS.COM



CHAMPION BRANDS, LLC // CLINTON, MO // 800-821-5693 // SINCE 1956

REV 01/20