

CHAMPION 2-CYCLE ENGINE OIL

CHAMPION 2 CYCLE ENGINE OIL is our premium quality dispersant motor oil. Built to exceed the requirements of leading engine manufacturers.

Directions: Mix only according to the manufacturer's recommended mixing ratio.

Super tough film oil protects against engine wear, and corrosion Superior anti-scuffing protection Increases performance by reducing engine deposits, carbon and spark plug fouling

Recommended for use where manufacturer specifications require 2-Cycle oil to meet

Recommended for use where manufacturer specifications require 2-Cycle oil to meet performance requirements of API TC. his specially formulated oil meets the lubrication and high temperature requirements of chain saw and other high performance 2 cycle engines requiring API TC service level.



PART# 4025 PART# 4425

Available in:

4025J - 8 Oz. 4025H - 1 Quart 4425V - 2.6 Oz.



TYPICAL PROPERTIES:

PRODUCT CODE:	4025
COLOR	GREEN
GRAVITY API @ 60°F	31.0
FLASH POINT °F	500
POUR POINT °F	-18
VISCOSITY @ 40°C, cSt	86.5
VISCOSITY @ 100°C, cSt	10.4
SUS @ 104°F	400
SUS @ 210°F	61
PRODUCT CODE:	4425
COLOR	GREEN
GRAVITY API @ 60°F	31.0
FLASH POINT °F	500
POUR POINT °F	-18
VISCOSITY @ 40°C, cSt	86.5
VISCOSITY @ 100°C, cSt	10.4
SUS @ 104°F	400
SUS @ 210°F	61

FOR HEALTH / SAFETY INFORMATION - REFER TO THE SDS at WWW.CHAMPIONBRANDS.COM

